



170KMFH-R Indirect Fired Multi Fuel Heater



Efficient, versatile and reliable, the 170KMFH-R portable indirect fired multi fuel heater produces clean, dry, safe heat offering an ideal environment for a variety of special event, emergency, and disaster response applications. The duct-in/duct-out solution uses far less fuel than a single duct-in solution and because the 170KMFH-R is an "In-direct" fired heater it does not introduce carbon monoxide or moisture into the heated area. Unit burns kerosene, filtered #1 and #2 diesel fuel and JP8 (Jet A Fuel). The unit comes complete with Remote Temperature Controller, Cable (32') and High-Quality PVC Ducting (max length 25'). Unit is available with optional Protective Crash Cage.

TECHNICAL SPECIFICATIONS:

HEATING CAPACITY	70,000 btu/h
HEATING	20.5KW
CONDITIONED AIR SUPPLY	910 CFM / 1546 m3/h
DIMENSIONS	44.5"L X 19"W X 24"H
WEIGHT	84lbs
FUEL TYPES	DF1, DF2, DFA, J
FUEL CONSUMPTION	0.55 gal/h
RUNTIME	21 hours/tank
FUEL TANK	11.6 gal or 43.91 liters
DUCT PORTS (2)	12" SUPPLY, 12" RETURN
VOLTAGE	120V/1/60
RUNNING LOAD AMPS	3
RUNNING LOAD WATTS	360

TECHNICAL SPECIFICATIONS CONT:

PLUG TYPE 15A STANDARD PLUG

FEATURES

- ~STAINLESS STEEL BURN CHAMBER
- ~AUTO SAFETY CONTROL DEVICES
- ~ELECTRONIC FLAME CONTROL
- ~POWDER COATED CABINET
- ~UL LISTED US/C

